ARTech Laboratory, Inc. Checklist

Feet, Partial Feet, Forefeet, and Toes

<u>Dental stone</u> model of lattected side, taken in the full weight bearing position with the
leg vertical. Model should be made 3 to 4 inches above ankle. See "Important Tips" or
<u>web site.</u>
Lab Plaster (not plaster bandage) model of "sound" side, taken in the full weight
bearing position with the leg vertical. Model should be made 2 to 3 inches above the
ankle. Also, a tracing of sound side.
Measurements filled out on Work Order
Color choices filled out on Work Order
Toes will be split for sandals unless otherwise noted.
<u>Very Important</u> : provide smallest shoes that patient would like prosthesis to fit into.
What will fit into a tennis shoe will probably NOT fit into a dress shoe. Silicone doesn't
compress like flesh.
Color-true photos taken on the ARTech background. If photos are taken from the Color
Chart printed from our web site, please include it with models. We need both a top and bottom
view, both sides, and a close up of the nails without polish. See "Photo Policy" on web site.
Make note of any additional information, like sensitive spots, extra support, build up, etc.
on the Work Order and model

BK's and AK's

Lab Plaster model (not plaster bandage) of "sound" foot, 3 to 4 inches above the ankle,
and taken in the weight bearing position.
Socket with foam sculpted to match shape of patient's leg. We do not have foam shaping
tools, nor do we know the shape of the patient's leg. Also a tracing of the sound foot. See
"Important Tips" on the web site.
Toes will be split unless otherwise noted.
Measurements filled out on Work Order
Shoe size – foot shell should be <u>two sizes smaller</u> .
Color choices filled out on Work Order.
Color-true photos taken on the ARTech Color Chart background by email, prints or USB.
If photos are taken using a Color Chart printed from our web site, please include it with models.
If prints, compare to patient's skin tones and circle the areas that most closely match. We need a
view from all angles and a close up of the nails without polish. Please include photos of the
upper leg also, especially if it is an AK. See "Photo Policy" on web site.

If patient has had a prosthesis previously, it would be helpful to us to have it, or at least a photo of it. They usually want the new prosthesis to look similar to the one they are using now unless there is some problem with the current one.

We do not need a lot of photos that are different colors. One or two prints of each angle, if they are color-true, will be sufficient.

It is not necessary to return the color chart with the models, unless it was printed off our web site.

When fabricating sockets, please try to duplicate the patient's sound side measurements as closely as possible and allow for 2mm thickness of silicone skin.

The very best way to ship stone models is to wrap them (after drying) in a bubble.